



DR2000-BLG

Product Name: Decomurale DR2000-BLG (457g/m2) Type II

Description:

Commercial grade printed vinyl wallcovering media – Textured beads that sparkle from tiny silver particles

- Simulates the look of a bed of small glass beads
- Can add a metallic brilliance to typical inkjet colors
- Heavy texture, rough surface, variable sparkle effect
- Has a light grey appearance because of silver sparkle coating

Construction:

Embossed vinyl face with laminated fabric backing. Backing is polycotton woven

Packaging:

3” core, wound print side out, wrapped in poly-bag, shipped in heavy-duty cardboard tube

Installation:

Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.

Availability:

54”, 60”

DR2000-BLG

Weight & Thickness: 20oz. per lineal yard (13 oz. per sq yd) 0.017in to 0.027in.

Metric 1.37m, 1.52m, 1.91m 30m, 50m, 100m .686m x 4.57m

Metric 457g/m² 0.432mm to 0.686mm

2

Type II Properties:

Passes all criterion for WA 101 Type II properties including: Break
Strength Shrinkage Washability

Tear Strength - Stain Resistance - Scrubability - Cold Crack - Coating Adhesion (Bond)
Blocking

Specifications:

Federal Specification:

CCC-408-D Type II*

WA Specification:

WA-101 , NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101*

Fire Test Ratings:

ASTM-E84 Tunnel Test Passed Class A

EU Class Flame (EN15102) Passed Class B, s2

BS476 Parts 6&7 Passed All Requirements CAN/ULC-S102

Passed All Requirements

Mold/Mildew:

ASTM-G21 Specifications Passed All Requirements

DR2000-BLG

Sustainability:

NSF-342 - Certified for Silver compliance for all DR2000 wall covering constructions

HPD – Health Product Declaration available

EPD – Environmental Product Declaration available - UL third party certified for wallcovering industry average

Low VOC– Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation

Prop 65 compliant

Manufactured without the use of Brominated flame retardants

For non-woven backed constructions –

11% post-consumer content in total product – using recycled polyester, cellulose 100% of backing fiber content is post-consumer fiber

Warranty: 5 Year Warranty against manufacturing defects.

Comments: *Meets or exceeds requirements for flame spread, smoke developed and flashover.