



DR2000-CC

Product Name: Decomurale DR2000-CC

Description:

Commercial grade printed vinyl wallcovering media - Luxurious multi directional grain

- Creates subtle light refraction and can provide small highlights of sheen when viewed at an angle
- Compliments almost any design graphic
- Light depth texture, rough surface, low gloss

Construction:

Embossed vinyl face with laminated fabric backing. Backing is polycotton woven or polyester/pulp non-woven depending on emboss

Packaging:

3" core, wound print side out, wrapped in poly-bag, shipped in heavy-duty cardboard tube

Installation:

Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.

Availability:

54", 60"

DR2000-CC

Weight & Thickness: 20oz. per lineal yard (13 oz. per sq yd) 0.017in to 0.027in.

Metric

1.37m, 1.52m, 1.91m 30m, 50m, 100m .686m x 4.57m

Metric

457g/m² 0.432mm to 0.686mm

Type II Properties:

Passes all criterion for WA 101 Type II properties including: Break Strength Shrinkage Washability
Tear Strength - Stain Resistance - Scrubability - Cold Crack - Coating Adhesion (Bond) Blocking

Specifications:

Federal Specification:

CCC-408-D Type II*

WA Specification:

WA-101 , NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101*

Fire Test Ratings:

ASTM-E84 Tunnel Test	Passed Class A
EU Class Flame (EN15102)	Passed Class B, s2
BS476 Parts 6&7	Passed All Requirements CAN/ULCS102
Passed All Requirements	

DR2000-CC***Mold/Mildew:***

ASTM-G21 Specifications Passed All Requirements

Sustainability:

NSF-342 - Certified for Silver compliance for all DR2000 wall covering constructions
HPD – Health Product Declaration available

DR2000-CC

EPD – Environmental Product Declaration available - UL third party certified for wallcovering industry average Low VOC – Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation

Prop 65 compliant

Manufactured without the use of Brominated flame retardants

For non-woven backed constructions –

11% post-consumer content in total product – using recycled polyester, cellulose 100% of backing fiber content is post-consumer fiber

Warranty: 5 Year Warranty against manufacturing defects.

Comments: *Meets or exceeds requirements for flame spread, smoke developed and flashover.