



## **DR2000-CF**

**Product Name:** Decomurale DR2000-CF

### **Description:**

Commercial grade printed vinyl wallcovering media –copper finish with highly reflective surface and super fine vertical brush marks

- Distinguished look and feel, shiny and reflective like our other Flash products
- Features super fine vertical brush marks
- No texture, smooth surface, high gloss
- Has a copper colored surface

### **Construction:**

Polyester/vinyl face with non-woven backing

### **Packaging:**

3” core, wound print side out, wrapped in poly-bag, shipped in heavy-duty cardboard tube

### **Installation:**

Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.

## DR2000-CF

**SPECIAL INSTALLATION INSTRUCTION** This wallcovering contains metallic particles and can conduct electricity. To avoid possible fire hazards or electric shock, wallcovering should not come in contact with or extend into electrical outlet boxes or light-switch boxes. Turn off all electricity to the room prior to starting installation.

**SPECIAL NOTE :** Please be aware this wallcovering may interfere with broadcast signals, such as Wi-Fi and radio reception, because of the polyester/metal layer. Tests have shown 5% or less impact on signals when the receptor is totally encased in wallcovering but the interference may vary depending on the specific installation conditions.

***Availability:***

54", 60"

***Weight & Thickness:***

20oz. per lineal yard (13 oz. per sq yd) 0.017in to 0.027in.

Metric

1.37m, 1.52m, 1.91m 30m, 50m, 100m .686m x 4.57m

Metric

457g/m<sup>2</sup> 0.432mm to 0.686mm

## **DR2000-CF**

### **Type II Properties:**

Passes all criterion for WA 101 Type II properties including: Break Strength Shrinkage Washability

Tear Strength - Stain Resistance - Scrubability - Cold Crack - Coating Adhesion (Bond) Blocking

### **Specifications:**

Federal Specification:

CCC-408-D Type II\*

WA Specification:

WA-101 , NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101\*

### **Fire Test Ratings:**

ASTM-E84 Tunnel Test	Passed Class A
EU Class Flame (EN15102)	Passed Class B, s2
BS476 Parts 6&7	Passed All Requirements CAN/ULC-S102
Passed All Requirements	

### **Mold/Mildew:**

ASTM-G21 Specifications	Passed All Requirements
-------------------------	-------------------------

## DR2000-CF

### ***Sustainability:***

NSF-342 - Certified for Silver compliance for all DR2000 wall covering constructions

HPD – Health Product Declaration available

EPD – Environmental Product Declaration available - UL third party certified for wallcovering industry average

Low VOC– Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation

Prop 65 compliant

Manufactured without the use of Brominated flame retardants

For non-woven backed constructions –

11% post-consumer content in total product – using recycled polyester, cellulose 100% of backing fiber content is post-consumer fiber

***Warranty:*** 5 Year Warranty against manufacturing defects.

Comments: \*Meets or exceeds requirements for flame spread, smoke developed and flashover.