



## DR2000-CV

**Product Name:** Decomurale DR2000-CV

**Description:** Commercial grade printed vinyl wallcovering media - Texture is a reproduction of painter's canvas

- Adds elegance to any wall
- Alternatively used for the Giclee and Fine Art business in digitally reproducing wall decor
- Medium depth texture, rough surface, low gloss

**Construction:**

Embossed vinyl face with laminated fabric backing. Backing is polycotton woven or polyester/pulp non-woven depending on emboss

**Packaging:**

3" core, wound print side out, wrapped in poly-bag, shipped in heavy-duty cardboard tube

**Installation:**

Standard commercial wallcovering pastes, primers and techniques. For indoor use in environmentally controlled spaces.

**Availability:**

54", 60"

## DR2000-CV

**Weight & Thickness:** 20oz. per lineal yard (13 oz. per sq yd) 0.017in to 0.027in.

Metric

1.37m, 1.52m, 1.91m 30m, 50m, 100m .686m x 4.57m

Metric

457g/m<sup>2</sup> 0.432mm to 0.686mm

Type II Properties: Passes all criterion for WA 101 Type II properties including: Break Strength Shrinkage Washability  
Tear Strength - Stain Resistance - Scrubability - Cold Crack - Coating Adhesion (Bond) Blocking

### **Specifications:**

Federal Specification:

CCC-408-D Type II\*

WA Specification:

WA-101 , NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101\*

### **Fire Test Ratings:**

ASTM-E84 Tunnel Test	Passed Class A
EU Class Flame (EN15102)	Passed Class B, s2
BS476 Parts 6&7	Passed All Requirements
S102	CAN/ULC- Passed All Requirements

### **Mold/Mildew:**

ASTM-G21 Specifications      Passed All Requirements

## DR2000-CV

### ***Sustainability:***

NSF-342 - Certified for Silver compliance for all DR2000 wall covering constructions

HPD – Health Product Declaration available

EPD – Environmental Product Declaration available - UL third party certified for wallcovering industry average Low VOC – Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation

Prop 65 compliant

Manufactured without the use of Brominated flame retardants

For non-woven backed constructions –

11% post-consumer content in total product – using recycled polyester, cellulose 100% of backing fiber content is post-consumer fiber

***Warranty:*** 5 Year Warranty against manufacturing defects.

Comments: \*Meets or exceeds requirements for flame spread, smoke developed and flashover.