

DR2000-MY

Product Name: Decomurale DR2000-MY

Description : Commercial grade printable vinyl wallcovering media - Described as a light cobweb texture that can simulate the look of hand painted brush strokes

- Suitable surface for almost any image
- Provides just enough texture to make your project stand out, without interfering with the printed design
- Light depth texture, smooth surface, low gloss

Construction : Embossed vinyl face with laminated fabric backing. Backing is polycotton woven or polyester/pulp non-woven depending on emboss

Packaging: 3" core, wound print side out, wrapped in black poly-bag, shipped in heavyduty cardboard tube

Availability: 54", 60"

Product Weight & Thickness: 20oz. Per linear yard (13 oz. per square yard) 0.017in to 0.027in.

Metric

1.37m, 1.52m, 1.91m 30m, 50m, 100m .686m x 4.57m

Metric

457g/m² 0.432mm to 0.686mm

DR2000-MY

Type II Properties:

Passes all criterion for WA 101 Type II properties including:

Break Strength - Shrinkage - Washability - Tear Strength - Stain Resistance -
Scrubability - Cold Crack - Coating Adhesion (Bond) - Blocking - Heat Aging
Colorfastness - Crocking

Specifications:

Federal Specification:

CCC-408-D Type II* WA

Specification:

WA-101 , NSF/ANSI 342 Sustainability Standard NFPA Life Safety Code 101*

Fire Test Ratings:

ASTM-E84 Tunnel Test	Passed Class A
EU Class Flame (EN15102)	Passed ClassB, s2
BS476 Parts 6&7	Passed All Requirements
CAN/ULC-S102	Passed All Requirements

Mold/Mildew:

ASTM-G21 Specifications	Passed All Requirements
-------------------------	-------------------------

DR2000-MY

Sustainability:

NSF-342 - Certified for Silver compliance for all DR2000 wallcoverings

HPD – Health Product Declaration available

EPD – Environmental Product Declaration available - UL third party certified for wallcovering industry average

Low VOC - Meets California CDPH Standard for Schools and Offices when tested to CA 01350

Contributes to LEED v4

Meets or exceeds EU Toxicity standard EN 12149 A,B,C for heavy metals and formaldehyde

Phthalate free formulation

Manufactured without the use of Brominated flame retardants

For non-woven backed constructions –

11% post-consumer content in total product – using recycled polyester, cellulose 100% of backing fiber content is post-consumer fiber

Warranty:

5 Year Warranty against manufacturing defects.

Comments:

*Meets or exceeds requirements for flame spread, smoke developed and flashover.