

## SGC4000-L2

**Product Name:** Decomurale SGC4000-L2

**Description:** Optically clear polyester film for glass applications. Printed with UV curable eco inks. White ink available for creating design patterns and frosted films with use of transparency.

Packaging: 3 inch core, printed face rolled on the outside, wrapped in polybag, shipped in a solid tube or box.

**Installation:** Standard window film installation techniques. For indoor use in controlled environment spaces.

**Availability:** 48", 60"

**Thickness :** 2 mil

**Warranty :** 5 year warranty on manufacturing defects.

### Specifications :

% Total Solar Transmittance : 83  
 % Total Solar Reflectance : 8  
 % Total Solar Absorptance : 9  
 % Visible Light Transmittance : 89  
 % Visible Reflectance (outdoors) : 9  
 % Visible Reflectance (indoors) : 9  
 Winter U-value : 1.07  
 Shading Coefficient : 0.99  
 % Ultraviolet Ray Protection (wavelengths 300-380nm) : 94  
 Émissivity: 0.90  
 Solar Heat Gain Coefficient: 0.86  
 %Solar Energy Rejected: 14  
 Light to Solar Heat Gain Ratio (LSG) : 1.03  
 %Summer Solar Heat Gain Reduction: 0  
 %Winter Heat Loss Reduction: -3  
 % Glare Reduction: 1